



E006: Temperature monitoring devices

PQS code:	E006/101
Description:	30 day temperature logger
Manufacturer's ref:	LM Pro FZT (Type 1)
Manufactured in:	India
Company:	G-Tek Corporation Private Limited
Address:	3, MAHAVIR INDUSTRIAL ESTATE NEAR JALARAM MANDIR, Karelibagh, Vadodara - 390018 Gujarat, India
Telephone:	+91 98 242 61702
Email:	asu@gtek-india.com
Web address:	www.gtek-india.com

Specifications

Product type:	30-day electronic refrigerator temperature logger	Display medium:	LCD display
Mode of operation:	Electronic	Weight	0.1 kg
Minimum temperature:	-30	Main material:	Polycarbonate plastic; non-breakable, non- corrodible
Maximum temperature:	+60 °C	Dimensions:	12.8 (L) x 6.0 (W) x 2.2 (H) cm
MECHANICAL AND ELECTRONIC DEVICES ONLY			
Accuracy:	± 0.5 °C for the range -30 °C to + 30 °C ± 0.7 °C otherwise	Min logging interval:	1 minute (5 minutes prefixed)
Power source:	Lithium Coin Cell Battery	Alarm type:	Visual
Battery type:	Non-Replaceable 3.0V 950 mAH, CR2477 Coin Cell Bat	User interface:	LCD and Keyboard Interface
Battery shelf life:	5.5 years	Programmability:	Factory programmed
Activated life:	60 months	IP rating:	IP64
Memory capacity:	17280 records	<p>The LMPro FZT (Type-1) Data logger is an Integrated Sensor 30 days temperature logger meeting the requirements of WHO/PQS/E006/TR06.4 specification protocol.</p> <ol style="list-style-type: none"> 1. Manual Start, by pressing "Up" key for about 2 seconds. 2. Start delay of 30 minutes 3. Once started device cannot be stopped 4. Device can be PAUSED to exclude data from alarm, min/max statistics for 15 minutes while recording will continues, auto resume from PAUSE after 15 minutes 5. Direct PDF/CSV Summary Report of maximum 60 days can be generated by connecting the device with PC using USB2.0 Type C data cable 6. User can view last 30 days of history data on the device display using keyboard 7. Total of 60 days of storage 8. Memory Roll-over after 60 days of storage 9. Multi digit, character LCD display to indicate various functions, parameters and values 10. Display dimension: 22 x 42 mm; 0.35" HTN Reflective 11. Display Auto-off; after 20 seconds of non-access of Keyboard 12. LED status indicator for RUN mode 13. Three front panel keys to perform various functions <p>For more details refer to the operating manual and quick start guide</p>	
Comments:			
Minimum order:	1	Year base price:	2025
Quality standard:	- ISO 9001:2015 - Other -	Pieces per carton:	40
Price per unit:	For 1-100 units US\$65 per unit For 101-250 units: Consult Factory For more than 250 units: Consult Factory	Volume per carton:	0.049
		Weight per carton:	9
		Incoterms:	EXW
Verification report:	LLTPL/TL/2024-08/01	Verification laboratory:	Lisaline Lifescience Technologies PVT. LTD
Current PQS status:	<i>pre-qualified ; 28 Mar 2025</i>		Valid until:
Note: If Current PQS status is 'Suspended' or 'Withdrawn', this product is NOT to be purchased.			